

Products

SERIES 2510 / 2500D



SPEC

MODEL		SERIES 2510	SERIES 2500D
Overall Size		755(W) x 1,730(H) x 1,470(L)mm	730(W) x 1,730(H) x 1,500(L)mm
Chamber	Size	500(W) x 500(H) x 1,000(L)mm	
	Material	Stainless Steel 316L	

	Capacity	250ℓ
Heater	Power	AC 3P 380V / 220V, 18Kw
	Material	Alloy
Shelves	Size	480(W) x 950(L)mm 2EA
	Material	Stainless Steel 316L
Temperature Range		110°C~135°C (230°F~275°F)
Water Supply		15A, Water pressure 1~3Kgf/kgf/cm²
Control system		Microprocessor (AVR)
Self-Control		Auto Test Mode
Display		Color 5.7' TFT-LCD Touch Screen
Dry System		Watering Vacuum Pump
Power Consumption		AC 1P 220V and 3P 380V, 50/60Hz, 18Kw

INFORMATION

1. Design & Material

The Series 2510/2500D is Steam Sterilizer with the designation and production by A.S.M.E Regulation.

2. Self-test Function

Checking the whole conditions prior to operation with self-diagnostic function.

Happening malfunction, operation stopping, beeping and displaying the "ER" and "Error Number"

3. Safety Valve

Safety Valve- prevent from overpressure.

Door interlock system-if the chamber pressure is over 30kpa, the door is not opened by mechanical door lock system.

4. Drying System

Vacuum system by Steam/Water Ejector.

5. Automatic operation

Easy operation with the implementation of full Automatic system by microprocessor.

6. Air filter

Re-pollution controlling by accepting new filter that can filter the particles of $0.3\mu\text{m}$ up to 99.98% and filtering air inflowing to chamber from outside at the process of drying cycle.

7. 5.7" LCD Color Touch Screen/High quality and Bright color display.

DELTA MS CORP CEO : Jeong Kwon Seo's

Address : 4-8, Gyehyangbuk-gil, Jeongnam-myeon, Hwaseong-si, Gyeonggi-do, Republic of Korea (18519) TEL. +82 31-416-2671 FAX. +82 31-416-2679

Copyright © 2013 DELTA MS All rights reserved.