

Products

SERIES 410



SPEC

MODEL		SERIES 410
Overall Size		580(W) x 430(H) x 640(L)mm
Chamber	Size	310(W) x 310(H) x 450(L)mm
	Type	Rectangular

	Capacity	43ℓ
Heater	Sheath Heater	AC 220V, 2.2Kw
	Material	Stainless Steel
Tray	Size	300(W) x 50(H) x 410(L)mm
	Material	Stainless Steel
Temperature Range		110°C~135°C (230°F~275°F)
Reservoir Capacity		5ℓ
Control System		Microprocessor
Door Lock System		Mechanical CAM Type
Power Consumption		AC220V, 50/60Hz, 2.2Kw
Accessories		Cart : 580(W) x 750(H) x 630(L)mm
Weight		76Kg

INFORMATION

1. Characteristic

All of the working programs are set-up in micro-processor system. Automatic.
Cylindrical chamber type.

2. Door

Using the Aluminum alloy material.

Lock system is the method of cam rotate.

The Silicon Rubber using for Gasket without the leakage in constant press.

Door micro-Switch checks the door lock. Preventing the door open operation.

3. Air removal method -Gravity type and using the Steam Trap

4. Dry type- F.A.S.E System (Fully automatic Steam Ejector), Hot wind dry type.

5. Sounded the melody when the cycle is ended

6. Safety device

Thermostat – Preventing the Fire. Safety valve – Preventing Overpressure

Normal Open solenoid valve – Make the atmosphere when stop or Power off.

DELTA MS CORP CEO : Jeong Kwon Seo's

Address : 4-8, Gyehyangbuk-gil, Jeongnam-myeon, Hwaseong-si, Gyeonggi-do, Republic of Korea (18519) TEL. +82 31-416-2671 FAX. +82 31-416-2679

Copyright © 2013 DELTA MS All rights reserved.