

Products

SERIES 600



SPEC

MODEL		SERIES 600
Overall Size		620(W) x 480(H) x 840(L)mm
Chamber	Size	Φ350×650(L)mm
	Type	Cylindrical

MODEL STERILIZER		PRODUCTS	NEWS	ABOUT US	SERIES 600 CUSTOMER SERVICE	ENG
	Material		Stainless Steel			
	Capacity		63ℓ			
Heater	Sheath Heater		AC 220V, 2.7Kw			
	Material		Stainless Steel			
Tray	Size		214(W) x 30(H) x 443(L)mm			
	Material		Stainless Steel			
Temperature Range			110°C~135°C (230°F~275°F)			
Reservoir Capacity			7ℓ			
Control System			Microprocessor			
Door Lock System			Mechanical CAM Type			
Power Consumption			AC220V, 50/60Hz, 2.7Kw			
Accessories			Cart : 620(W) x 750(H) x 760(L)mm			
Weight			95Kg			

INFORMATION

1. Characteristic

All of the working programs are set-up in micro-processor system. Automatic.
Cylindrical chamber type.

Door lock system is Mechanical Cam type.

Air removal is Gravity type.

Heater is built in the chamber.

2. Door

Using the Aluminum alloy material.

Lock system is the method of cam rotate.

The Silicon Rubber using for Gasket without the leakage in constant press.

Door micro-Switch checks the door lock. Preventing the door open operation.

3. Air removal method -Gravity type and using the Steam Trap

4. Dry type- F.A.S.E System (Fully automatic Steam Ejector), Hot wind dry type.

5. Sounded the melody when the cycle is ended

6. Safety device

Thermostat – Preventing the Fire. Safety valve – Preventing Overpressure

Normal Open solenoid valve – Make the atmosphere when stop or Power off.

DELTA MS CORP CEO : Jeong Kwon Seo's

Address : 4-8, Gyehyangbuk-gil, Jeongnam-myeon, Hwaseong-si, Gyeonggi-do, Republic of Korea (18519) TEL. +82 31-416-2671 FAX. +82 31-416-2679

Copyright © 2013 DELTA MS All rights reserved.