



Products

SERIES 8000(D)



SPEC

MODEL		Series 6000(D)	Series 8000(D)
Overall Size		1,200(W) x 2,000(H) x 1,600(L)mm	1,200(W) x 2,000(H) x 2,000(L)mm
Door Type		Vertical Slide Type	
Chamber	Size	670(W) x 670(H) x 1,350(L)mm	670(W) x 670(H) x 1,800(L)mm

	Capacity	606ℓ	806ℓ
Jacket Material	Stainless Steel		
Temperature Range	110°C~135°C (230°F~275°F)		
Operation Cycle	Pre-Vacuum, Flash, Liquid, Gravity, Leak-Test, Bowie-Dick Test		
Printer	Thermal dot Matrix, 40 characters per line		
Control System	PLC or Embedded system		
Vacuum System	Vacuum with Watering Vacuum pump or Water Ejector		
Electric Consumption	1P 220V and AC 220/380V, 50/60Hz, 4Kw		
Display	Color 5.7" TFT-LCD Touch Screen		
Steam Source (Selcet)	House Steam Supply: Pipe ¾", Flow rate- Max 80kg/hr, Pressure 3.5~5Kgf/cm²		
Water Supply	½" above, Water Pressure 1~3Kgf/cm²		
Air Supply	¼" Air Pressure 4~6Kgf/cm²		
Drain Pipe	Copper or Steel(not metal 110°C), above 2"		
Weight	Approx. 1,300Kg	Approx. 1,800Kg	

INFORMATION

2. Fully Automatic Control equipped with PLC or Embedded system

Easy operation and control with the implementation of Full Automatic system by PLC or embedded system.

3. Safety Device of the system

Checking the whole conditions prior to operating with self-diagnostic function.

The Error message are showed on the display and sounded the alarm when the problem happen on the operation or the condition is not setting before the start.

Happening malfunction, operation stopping, Beeping and Displaying the "ER" and "Error Number"

Safety Valve- prevent from overpressure.

Door interlock system-if the chamber pressure is over 30kpa, the door is not opened by mechanical door lock system.

4. Vertical Sliding door

Vertical Sliding door is Easier Open and Close with Simple, Safe and Clean front.

Space is optimized because the Door does not swing outward.

5. Operator Easily Control by 5.7" TFT LCD Color Touch Screen

Display is the 5.7" TFT LCD color Touch Screen, which can select the operation cycle.

Large sized display to easily and clearly check the process for cycles from long distance.

Can be conversed in Korean or English.

Cycle process is displaying by blinking on the status.

Display the remaining Sterilization and Dry time (Countdown)

6. Each Analog Pressure Gauge

7. Vacuum System

The sterilization is initiated by a vacuum pump (or water ejector) generating a high vacuum to remove remaining air in the load on the Pre-vacuum and Flash Cycle.

The steam vapor is removed by vacuum system to improve load drying in the dry process.

Higher vacuum & Lower consumption of water by equipping watering-system pump.

8. Printer System

It prints out the data for user to judge and record the result of sterilize cycle.

The paper shows started sate and setting value of cycles.

Also shows critical information under the cycles (Time, Temperature, Pressure).

DELTA MS CORP CEO : Jeong Kwon Seo's

Address : 4-8, Gyehyangbuk-gil, Jeongnam-myeon, Hwaseong-si, Gyeonggi-do, Republic of Korea (18519) TEL. +82 31-416-2671 FAX. +82 31-416-2679

Copyright © 2013 DELTA MS All rights reserved.